

**VETRINE REFRIGERATE PIZZA STATICHE - G-VRX1400-380SS****CODICE:** G-VRX1400-380SS**DATI TECNICI**

|                                    |   |
|------------------------------------|---|
| <b>OPERATING TEMPERATURE</b>       | <u>+2°C/+8°C</u>  |
| <b>EXTERNAL DIMENSIONS</b>         | <u>1400 x 395 x 285/617(h) mm con coperchio chiuso/aperto</u> |
| <b>CAPACITY (L)</b>                | <u>4 x GN1/3 +1x GN1/2</u>                                    |
| <b>MAX. OPERATING TEMPERATURE</b>  | <u>+35°C / 50%HR</u>  |
| <b>TYPE OF COOLING</b>             | <u>statica</u>  |
| <b>DEFROSTING TYPE</b>             | <u>automatico</u>   |
| <b>TYPE OF COOLING GAS</b>         | <u>R600a</u>  |
| <b>SUPPLIED ACCESSORIES</b>        | <u>Kit acciaio inox</u>                                       |
| <b>CONDENSED WATER EVAPORATION</b> | <u>manuale</u>  |
| <b>TEMPERATURE CONTROL</b>         | <u>elettronico</u>  |
| <b>INSULATION (mm)</b>             | <u>45</u>   |
| <b>POWER CONSUMPTION (W)</b>       | <u>125</u>  |
| <b>VOLTAGE</b>                     | <u>220V-240V / 50Hz</u>                                       |

**CONSTRUCTION MATERIAL** acciaio Inox

**INTERIOR LIGHT** no

**GAS (gr.)** 35

Vetrine refrigerate pizza con refrigerazione statica. Coperchio di protezione per una migliore conservazione del cibo - gruppo incorporato solo lato destro gas R600a. Adatte per il contenimento di bacinelle gastronom inox o policarbonato - bacinelle escluse.

